

# ED Series Crane Scales

EDXtreme & EDjunior Crane Scales

DILLON

3

9

Units | Mo

ESC

5





BE

USA

Working Load Limit 5,000 lbf / 2000 kgf

ZERO



# ED Series Crane Scales

Guesswork is not acceptable. When you have people working around massive loads, there is no room for error. You have to have complete confidence in the strength and the accuracy of your measurement tools.

Since 1937, Dillon Dynamometers have been chosen for the jobs where only the best will do. Now, Dillon has once again lifted the performance bar and set the standard for others to follow — Dillon ED Series Crane Scales.

Two ED Series models are available: The high-end EDXtreme (also called EDX), and the affordable EDjunior. Choose EDXtreme for the most demanding applications; EDxtreme is built with the best materials and designed with cutting-edge features like radio control. Where cost is a concern, and reliability is a requirement, choose EDjunior – the perfect crane scale for simple jobs.

# EDXtreme – The ultimate in reliability & accuracy



Specifications and dimensional details are available from an authorized Dillon Distributor or the website at www.dillonforce.com.

# Xtreme accuracy: 0.1%

Accurate repeatable readings are essential to proper weighing. The higher standards set for the EDx Crane Scales meant taking the time to ensure that material characteristics, load element design and strain gage meshed perfectly. The result of that effort is a typical accuracy of 0.1% of full scale capacity. The enhanced resolution mode of 1 part in 5000 provides the level of readability needed for refined weighing.

#### Xtreme ease

- **Exclusive SOFTKEY interface** Eliminates confusing menus for faster setup and simple operation.
- **Local gravity correction** Unit adjusts to local gravitational conditions, without recalibration.
- **Custom units of measure –** User-defined units of measure mean the instrument adapts to changing requirements.
- Wide-angle, backlit LCD Provides improved readability over a wider viewing angle and has backlighting for low light conditions.
- **Battery operation** Powered by two standard C-cell batteries. Batteries are easily accessible for fast replacement.

# Xtreme engineering

Building a precision instrument that can survive realworld punishment requires masterful engineering. This is where Dillon's experience shines through. The engineers assigned to the EDx Crane Scale drew on a depth of industrial application knowledge and conducted exhaustive materials testing to achieve the highest structural integrity.

- Superior strength and corrosion resistance High capacity models are constructed of powder coated aircraft-quality alloy steel. Lower capacity models are powder coated aircraft-quality aluminum.
- 5:1 factor of safety\* This measure of strength and safety is maintained at all capacities. Computer modeling confirms the low stress and long product life that is inherent in the EDXtreme Crane Scale design.
- NEMA 4X/IP55 The EDXtreme is clearly the choice for reliability in any environment – in-plant or out on the job site.

\* Models with 75 T/160,000 lb or higher capacity feature a 4:1 safety factor and 0.3% accuracy.

DILLON

52290 TOTA Units | Mode | Print

ESC

Δ

pars

7

+1-

Displa

2

5

8

3

6

9

1/0

ON / OFF

Force Ib

# Expandable Scale Network

A basic stand-alone model can be easily upgraded "in-the-field" to accommodate changing needs. Remote configuration, data acquisition and single point monitoring of multiple links are all possible with the hardwired or radio communication options available with the EDXtreme Crane Scale. An RS-232 interface is standard on both the EDXtreme and Communicator for connection to a host PC.

#### **Typical Configurations**

- **1.** Stand-alone EDx for direct measurement applications.
- 2. Single network with one EDx radio Crane Scale and Communicator.
- **3.** Single network with multiple EDx Crane Scales and one Communicator. The Communicator monitors the load at each scale, plus the total weight.
- **4.** Single network with two, three or four Communicators.
- 5. Multiple networks with multiple EDx Crane Scales and Communicators.



**Optional Remote Communicator** 

II showing four crane scale

readings and total of all.

**The EDjunior is all about value.** Behind its simple design and easy operation, you will find the quality and performance not found elsewhere. With the EDjunior, Dillon proves that economy can go hand-in-hand with accuracy, long service life and, most importantly, worker safety – just compare the Dillon EDjunior to the competition. Nothing else comes close!

#### Measurement Capabilities

The EDjunior provides peak detection as well as live load readings. Selectable units of measure include lbf, kgf and Newtons.

**Accuracy** — The load element design and strain gauges chosen for the EDjunior produce an accuracy of 0.2 % (full scale). This level of precision offers flexibility for use in a broad range of applications. Capacities up to 10,000 lb (5000 kg) available.

**Resolution** — Readings are displayed with a resolution of 1 part in 1000 to ensure the level of readability required for critical lifting applications.

#### **Control Interface**

The exclusive Dillon SOFTKEY interface provides direct access to setup and display functions without the typical confusing menu structure. The 6-digit dot-matrix display features 1 inch (25 mm) high numerals for greater visibility.

#### High Strength, Low Weight

Heavy, cumbersome tools make tough jobs even harder. Through the use of aircraft quality materials, Dillon has made the EDjunior an easy-to-position, highly mobile instrument with exceptional strength. It offers an impressive factor of safety at all capacities.

#### All Environments

With its NEMA4/IP55 design, the EDjunior is at home in virtually any environment and ideally-suited to outdoor job-site applications as well as in-plant use.



Specifications and dimensional details are available from an authorized Dillon Distributor or the website at www.dillonforce.com.



### Dillon on the job

Dillon force measurement equipment is the preferred choice of public utilities, nuclear facilities, tower erectors, armed services and material handlers throughout the world. Dillon also manufactures mechanical crane scales, high accuracy mechanical and electronic dynamometers and overload protection devices.

#### **AUTHORIZED DISTRIBUTORS**

Ask the experts. Dillon distributors offer complete service capabilities from application assistance to sales and product support. Their experienced representatives are the most knowledgeable experts that you will find in the force measurement industry. We recommend that you consult these capable specialists for all of your measuring needs.

# R.D. Jacobs Company 500 Southeast Thirteenth Street Fort Lauderdale, Florida 33316 Phone: 954.462.1932 Fax: 954.527.4466 email: info@dynamometers.com



**Force Measurement Equipment** 

A division of Avery Weigh-Tronix, LLC



Dillon is part of Avery Weigh-Tonix. Avery Weigh-Tonix is a trademark of the Illinois Tool Works group of companies whose ultimate parent company is Illinois Tool Works Inc ("Illinois Tool Works"). Copyright © 2013 Illinois Tool Works. All rights reserved. This publication is issued to provide outline information only and may not be regarded as a representation relating to the products or services concerned. This publication was correct at the time of going to print, however Avery Weigh-Tonix reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service at any time.

1/14 EDCrane\_097386-0010\_L.indd (C&D) 097386-0010